



IDV26

DIRECT VENT GAS FIREPLACE INSERT



THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY

The unit illustrated is an IDV26N Direct Vent Insert – Natural Gas, LOGF27 Log Set, I26CV3BL Clean View – Black, and IDV26RL Brick Liner.



IDV26

DIRECT VENT GAS FIREPLACE INSERT



THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY

The unit illustrated is an IDV26N Vent Insert – Natural Gas, I26CVPF1BL Clean View Picture Frame – Black, LOGF27 Log Set, IDV26RL Refractory Brick Liner.

| | | |
|----------------------|-------------------|---------------------|
| Model | IDV26N IDV26NE | IDV26LP IDV26LPE |
| Fuel | Natural | Propane |
| Input | 30,000 BTU | 30,000 BTU |
| Low | 21,000 BTU | 25,000 BTU |
| FE (P.4.1-02) | 65.3% | 65.3% |

Convert your wood burning fireplace to gas, for a new standard of warmth, beauty, safety and convenience.

STANDARD FEATURES*

- Dual Burner with glowing embers
- Hi/low Millivolt or IPI valve system, will operate during power failures
- Matchless Piezo Ignition
- Decorative Ash Bed
- Ceramic Glass (Heat Radiating)
- On/Off Rocker switch
- Heat activated blower with variable speed control
- Safety Screen Barrier*



Safety Screen Barrier

OPTIONAL FEATURES

Log Set

Fibre Split Oak

Glass Tray with Bronze Glass

Clean View Kit

Black, Pewter, Copper Vein

Surrounds for Clean View

Black, Pewter, Copper Vein

Surround Picture Frame for Clean View

Black, Pewter, Copper Vein

Porcelain Reflective Liners

Brick Liner

Traditional

Wall Mount Thermostat

Standard On/Off or Programmable

Remote Control

On/Off, Thermostat On/Off, Thermostat On/Off modulating



CLEAN VIEW AND SURROUND SIZES (IN.)

| IDV26 | Width | Height | Depth |
|----------|----------------------------------|--|---------------------------------|
| I26CV1 | 35 ⁵ / ₈ " | 22 ³ / ₄ " | 1 ³ / ₄ " |
| I26CV2 | 44 ⁵ / ₈ " | 26 ⁵ / ₈ " | 1 ³ / ₄ " |
| I26CVPF1 | 35 ⁵ / ₈ " | 25 ⁷ / ₈ " | 1 ³ / ₄ " |
| I26CVPF2 | 44 ⁷ / ₈ " | 33 ¹ / ₂ " | 1 ³ / ₄ " |
| I26S1 | 42" | 27 ¹ / ₂ " | |
| I26SU | 47 ¹ / ₂ " | 35 ⁵ / ₈ " / 28 ⁵ / ₈ "* | |
| I26SU | 39 ³ / ₈ " | 29 ³ / ₄ " | |
| I26CV3 | 35 ⁵ / ₈ " | 22 ³ / ₄ " | 3 ¹ / ₂ " |

*Dimension as a three sided surround

MINIMUM FIREPLACE OPENING (IN.)

| IDV26 | Width | Height | Depth |
|-------|------------|----------------------------------|----------------------------------|
| IDV26 | 33" / 28"* | 19 ¹ / ₂ " | 14 ¹ / ₄ " |

*Components In (CV1) 33"; Components Out (CV2) 28"

MINIMUM UNIT COVERAGE – CLEAN VIEW

| IDV26 | Width | Height |
|-----------|----------------------------------|----------------------------------|
| I26CV1* | 34 ¹ / ₂ " | 22" |
| I26CV2* | 41 ¹ / ₂ " | 25 ¹ / ₂ " |
| I26CV3* | 34" | 22" |
| I26CVPF1* | 34 ¹ / ₂ " | 25" |
| I26CVPF2* | 41 ¹ / ₂ " | 32 ³ / ₈ " |
| I26CV1DS* | 34 ¹ / ₂ " | 22" |

*Back Frame Dimension of Clean View Kit



1. IDV26N Direct Vent Insert – Natural Gas, LOGF27 Log Set, I26CVPF2BL Clean View Picture Frame – Black, IDV26RL Refractory Brick Liner.



2. IDV26N Direct Vent Insert – Natural Gas, I26CV2PW Clean View Kit – Pewter, LOGF27 Log Set, IDV26RL Refractory Brick Liner.



3. IDV26N Direct Vent Insert – Natural Gas, I26CVPF1BL Clean View Picture Frame – Black, LOGF27 Log Set, IDV26PRL Porcelain Reflective Liner.



4. IDV26N Direct Vent Insert – Natural Gas, I26CV1CV Clean View Kit – Copper Vein, I26S1CV Surround – Copper Vein, LOGF27 Log Set, IDV26RL Refractory Brick Liner.



*Components may have to be ordered separately to create a complete unit. Discuss with your local Kingsman dealer for clarification.

Kingsman Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.



2340 Logan Avenue
Winnipeg, Manitoba, Canada R2R 2V3
Phone: (204) 632-1962 Fax: (204) 632-1960
www.kingsmanfireplaces.com

IDV26

DIRECT VENT GAS FIREPLACE INSERT



*Components may have to be ordered separately to create a complete unit. Discuss with your local Kingsman dealer for clarification.

Kingsman Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.
Certification: Certified for Canada/USA as a Vented Gas Fireplace Heater ANSI Z21.88-2014, CSA 2.33-2014, CGA 2.17-M91 (R2009).