



# IDV26

DIRECT VENT GAS FIREPLACE INSERT



THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY

Model IDV26N Direct Vent Insert – Natural Gas, LOGF27  
Log Set, I26CV3BL Clean View – Black, IDV26RL Brick Liner.



# IDV26

DIRECT VENT GAS FIREPLACE INSERT



THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY

Model IDV26N Vent Insert – Natural Gas, I26CVPF1BL Clean View Picture Frame – Black, LOGF27 Log Set, IDV26RL Refractory Brick Liner.

Model	IDV26N / IDV26NE	IDV26LP / IDV26LPE
Fuel	Natural	Propane
Input Max.	30,000 BTU	30,000 BTU
Input Min.	21,000 BTU	25,000 BTU
FE (P.4.1-15)	65.8% / 68%	65.8% / 68%

Convert your wood burning fireplace to gas, for a new standard of warmth, beauty, safety and convenience.

### STANDARD FEATURES

- Dual Burner with glowing embers
- Hi/low Millivolt or IPI valve system, will operate during power failures
- Matchless Piezo Ignition
- Decorative Ash Bed
- Ceramic Glass (Heat Radiating)
- On/Off Rocker switch
- Heat activated blower with ariable speed control
- Safety Screen Barrier



Safety Screen Barrier

### OPTIONAL FEATURES

#### Log Set

Fibre Split Oak

#### Glass Tray with Bronze Glass

#### Clean View Kit

Black, Pewter, Copper Vein

#### Surrounds for Clean View

Black, Pewter, Copper Vein

#### Surround Picture Frame for Clean View

Black, Pewter, Copper Vein

#### Liners

Porcelain Reflective Liner or Traditional Brick

#### Wall Mount Thermostat

Standard On/Off or Programmable

#### Remote Control

On/Off, Thermostat On/Off, Thermostat On/Off modulating



### CLEAN VIEW AND SURROUND SIZES (IN.)

IDV26	Width	Height	Depth
I26CV1	35 <sup>5</sup> / <sub>8</sub> "	22 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "
I26CV2	44 <sup>5</sup> / <sub>8</sub> "	26 <sup>5</sup> / <sub>8</sub> "	1 <sup>3</sup> / <sub>4</sub> "
I26CVPF1	35 <sup>5</sup> / <sub>8</sub> "	25 <sup>7</sup> / <sub>8</sub> "	1 <sup>3</sup> / <sub>4</sub> "
I26CVPF2	44 <sup>7</sup> / <sub>8</sub> "	33 <sup>1</sup> / <sub>2</sub> "	1 <sup>3</sup> / <sub>4</sub> "
I26S1	42"	27 <sup>1</sup> / <sub>2</sub> "	
I26SU	47 <sup>1</sup> / <sub>2</sub> "	35 <sup>5</sup> / <sub>8</sub> " / 28 <sup>5</sup> / <sub>8</sub> "*	
I26SU	39 <sup>3</sup> / <sub>8</sub> "	29 <sup>3</sup> / <sub>4</sub> "	
I26CV3	35 <sup>5</sup> / <sub>8</sub> "	22 <sup>3</sup> / <sub>4</sub> "	3 <sup>1</sup> / <sub>2</sub> "

\*Dimension as a three sided surround

### MINIMUM FIREPLACE OPENING (IN.)

IDV26	Width	Height	Depth
IDV26	33" / 28"*	19 <sup>1</sup> / <sub>2</sub> "	14 <sup>1</sup> / <sub>4</sub> "

\*Components In (CV1) 33", Components Out (CV2) 28"

### MINIMUM UNIT COVERAGE – CLEAN VIEW

IDV26	Width	Height
I26CV1*	34 <sup>1</sup> / <sub>2</sub> "	22"
I26CV2*	41 <sup>1</sup> / <sub>2</sub> "	25 <sup>1</sup> / <sub>2</sub> "
I26CV3*	34"	22"
I26CVPF1*	34 <sup>1</sup> / <sub>2</sub> "	25"
I26CVPF2*	41 <sup>1</sup> / <sub>2</sub> "	32 <sup>3</sup> / <sub>8</sub> "
I26CV1DS*	34 <sup>1</sup> / <sub>2</sub> "	22"

\*Back Frame Dimension of Clean View Kit



1.




2.



3.



4.



IDV26RL Traditional Brick Liner

LOGF27 Fibre Split Oak Logo Set

1. IDV26N Direct Vent Insert – Natural Gas, LOGF27 Log Set, I26CVPF2BL Clean View Picture Frame – Black, IDV26RL Refractory Brick Liner.
2. IDV26N Direct Vent Insert – Natural Gas, I26CV2PW Clean View Kit – Pewter, LOGF27 Log Set, IDV26RL Refractory Brick Liner.
3. IDV26N Direct Vent Insert – Natural Gas, I26CVPF1BL Clean View Picture Frame – Black, LOGF27 Log Set, IDV26PRL Porcelain Reflective Liner.
4. IDV26N Direct Vent Insert – Natural Gas, I26CV1CV Clean View Kit – Copper Vein, I26S1CV Surround – Copper Vein, LOGF27 Log Set, IDV26RL Refractory Brick Liner.



2340 Logan Avenue  
Winnipeg, Manitoba, Canada R2R 2V3  
Phone: (204) 632-1962 Fax: (204) 632-1960  
[www.kingsmanfireplaces.com](http://www.kingsmanfireplaces.com)

## IDV26

DIRECT VENT GAS FIREPLACE INSERT



Canada  
**ENERGUIDE**  
Look for the **ENERGUIDE**  
Gas Fireplace Energy  
Efficiency Rating in this brochure  
*Based on CSA P.4.1-15*



\*Components may have to be ordered separately to create a complete unit. Discuss with your local Kingsman dealer for clarification.  
Kingsman Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.  
Certification: Certified for Canada/USA as a Vented Gas Fireplace Heater ANSI Z21.88-2014, CSA 2.33-2014, CGA 2.17-M91 (R2009).

Printed in Canada  
12/17 – B076



CRAFTED ENTIRELY IN CANADA, EACH KINGSMAN FIREPLACE IS BUILT TO THE HIGHEST STANDARDS AND MADE TO LAST.

Model IDV26N Direct Vent Insert – Natural Gas, RSP10 Glass Tray Support with Bronze Glass, IDV26PRL Porcelain Reflective Liner, I26CV1BL Clean View – Black, I26S1BL Surround – Black.