

# VFI25 VENTED GAS FIREPLACE INSERT





2340 Logan Avenue Winnipeg, Manitoba, Canada R2R 2V3 Phone: (204) 632-1962 Fax: (204) 632-1960 www.kingsmanfireplaces.com

Model Hi/Lo Fire Control Input Max. (NG) Input Max. (LP) Venting FE (P.4.1-15) VFI25N / VFI25LP Yes 25,000 – 17,000 BTU 25,000 – 17,000 BTU 4" 44,58%

## **STANDARD FEATURES**

- Millivolt valve system allows operation during a power failure with Hi/low heat and flame adjustment
- Blower with a thermostat controlled On/Off including variable speed control is standard on all models
- Spill Safety Switch in case of a blocked flue or downdraft, it will shut down the unit
- Dual burner system with glowing embers
- Bedroom and Bed Sitting Room approved
- Safety Screen Barrier



#### Log Sets

LOGC6 Five Piece Cast Split Oak Log Set with glowing ember chunks, or LOGC5 Four Piece Cast Split Oak

#### Grills

Available in Black

#### Surrounds Deluxe (3 piece) Black with Black trim

Black with Black trim

# Risers for Deluxe Surrounds

Increases height coverage by 2 1/2"

## Thermostat

Wall Mount Millivolt Thermostat or Programmable Thermostat

## **Remote Control**

On/Off, Thermostat On/Off, Thermostat On/Off modulating, Thermostat On/Off modulating





mplete unit. Discuss with your local Kingsman dealer for clarification. refinement and improvements of all its products. Some aspect of units shown here may

Safety Screen Barrier

### LOGC5 Split Cast Log Set

Model VFI25N Vented Fireplace Insert – Natural Gas, with V25S2640B Surround Deluxe – Black V25T2640B Trim Black, V2R2640 Riser for Deluxe Surround VI20GBL Grills – Black and LOGC5 Log Set – Four Piece Split Oak Set. The Ultimate in Vented Fireplace Inserts, convert your wood burning fireplace to gas.


| 19"

## **INSERT DIMENSIONS**

VFI25 A 15 <sup>1</sup>⁄<sub>2</sub>" D 14" G 8 <sup>1</sup>⁄<sub>4</sub>" B 14" E 24 <sup>1</sup>⁄<sub>4</sub>" H 16 <sup>3</sup>⁄<sub>4</sub>"

C 20 ½"

F 26 ¼"




## **3 PIECE SURROUND DIMENSIONS (IN.)**

Models <b>DELUXE</b>	Height	Width	Part#	
VFI25	24 <sup>13</sup> / <sub>16</sub> "	36 <sup>13</sup> / <sub>16</sub> "	V25S2436B	
DELUXE	26 <sup>13</sup> /16"	40 ³/16″	V25S2640B	

## MINIMUM SIZE FOR INSTALLATION (IN.)

Models	Front Width	Rear Width	Height	Depth
VFI25	24″	20 <sup>1</sup> /2"	17 <sup>1</sup> /2"	16"



Based on CSA P.4.1-15

Kingsman F be changed ntertek Certificatio



Printed in Canada 03/18 - B042