



## IDV33/IDV43

DIRECT VENT GAS FIREPLACE INSERT



THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY

Model IDV33N Direct Vent Fireplace Insert – Natural Gas, LOGF35 Log Set – Fibre Split Oak, I33CV3BL Clean View Kit – Black.



## IDV33/IDV43

DIRECT VENT GAS FIREPLACE INSERT

Convert your wood burning fireplace to gas, for a new standard of warmth, beauty, safety and convenience.



### STANDARD FEATURES

- Dual Burner with glowing embers
- Millivolt or IPI valve system allows operation during power failure with Hi-Low heat and flame adjustment
- Decorative Ash Bed
- Ceramic Glass
- On/Off Rocker switch
- Heat activated blower with variable speed control
- Bedroom and bed sitting room approval
- Mobile home, bedroom and bed sitting room approval
- Safety Screen Barrier

### OPTIONAL FEATURES

#### Clean View Kit

Black (I33CV/I43CV1 Pewter and Copper Vein available)

#### Front Frame

Required for CV5 Cleanview

#### Surrounds for Clean View

Black (I33SR2/I43S4432 Pewter and Copper Vein available)

#### Surround Picture Frame for Clean View

Black

#### Louver Kit

Black Grills

#### Surrounds for Louver Kit

Black

#### Porcelain Reflective Liner

#### Brick Liner

Traditional and Herringbone (IDV43 only)

#### Log Set

Fibre Split Oak

#### Glass Tray


Ember Glass (Bronze)

#### Wall Mount Thermostat

Standard On/Off or Programmable

#### Remote Control


On/Off, Thermostat On/Off, Thermostat On/Off modulating



Traditional  
Brick Liner RLT



Herringbone  
Brick Liner RLH



Safety Screen Barrier



THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY

Model IDV43 Direct Vent Insert – Natural Gas, I43CV5BL Clean View Kit – Black, I43SF1BL Door Frame, I43S4432BL Surround – Black, LOGF36 Oak Log Set, IDV36RL Traditional Brick Liner.



<b>Model</b>	IDV33N / IDV33NE	IDV33LP / IDV33LPE	IDV43N / IDV43NE	IDV43LP / IDV43LPE
<b>Fuel</b>	NATURAL	PROPANE	NATURAL	PROPANE
<b>Input Max.</b>	31,000 BTU	28,500 BTU	34,250 BTU	30,000 BTU
<b>Input Min.</b>	20,900 BTU	23,100 BTU	24,000 BTU	22,840 BTU
<b>FE (P.4.1-15)</b>	50.43% / 51.74%	56.26% / 58.34%	60.18% / 61.7%	60.2% / 61.85%
<b>Flue Sizes</b>	3/3"	3/3"	4/3"	4/3"



1. Model IDV33LP Direct Vent Fireplace Insert – Propane, LOGF35 Split Fiber Oak Log Set, I33CVCV Clean View Kit – Copper Vein, I33SS1CV Surround for Clean View – Copper Vein, IDV33RL Refractory Brick Liner.
2. Model IDV33LP Direct Vent Fireplace Insert – Propane, LOGF35 Split Fiber Oak Log Set – I33CVPW Clean View Kit – Pewter, I33SS1PW Surround for Clean View – Pewter, IDV33RL Refractory Brick Liner.
3. Model IDV43N Direct Vent Insert – Natural Gas, I43LK Louver Kit, LOGF36 Log Set, IDV36RLT Refractory Brick Liner – Traditional.

#### MINIMUM FIREPLACE OPENING (IN.)

Model	Width	Height	Depth	Model	Width	Height	Depth
IDV33	26 1/4"	21 3/8"	14 3/8"	IDV43	30 3/4"	25 5/8"	14 3/4"

#### LOUVER KIT AND SURROUND SIZES (IN.)

IDV33	Width	Height	IDV43	Width	Height
I33LK (Louver Kit)	34 1/2"	24 3/8"	I43LK (Louver Kit)	39"	28 3/4"
I33S3426 (Surround)	34 1/2"	26 1/2"	I43LKS1BL	39"	31 3/4"
I33S4028 (Surround)	40"	28 1/8"	I43LKS2BL	44"	32 3/8"
I33S4430 (Surround)	44"	30 5/8"	I43US4736BL	47"	36"
I33S4535 (Surround)	45"	35"			

#### CLEAN VIEW AND SURROUND SIZES (IN.)

**Minimum Fireplace Opening: 26 3/8" W x 21 3/8" H x 14 3/8" D**

IDV33 INSERT	Width	Height	Depth
I33CV (Clean View)**	33 3/8"	23" / 24 5/16"	2 1/2"
I33CV3 (Clean View)**	33 3/8"	23 1/8" / 24 5/16"	4 1/8"
I33SR2 (Surround)	39"	27"	5/8"
I33SRP3 (Surround Picture Frame)	41"	31"	5/8"
I33USR4 (Surround Universal)	45"	35"	1 1/16"
I33CV5 (Clean View)	37 1/8"	25 1/4"	2 5/16"
I33BT1 (Back Trim Surround)*	39"	26"	1 1/4"
I33USR4 (Surround Universal)	45"	35"	1 1/16"
I33CVPF5 (Clean View Picture Frame)	37 1/8"	25 1/4"	2 5/16"
I33BTPF (Back Trim Surround)*	41"	31"	1 1/4"

\* Back Trim Surround required if the fireplace opening is smaller than 29 3/8"W x 22 3/8"H x 16 1/8"D.  
Note: When Using I33CV5/I33CVPF5 Clean View a Door Frame is Required.

\*\*CV and CV3 have a tapered profile.

#### Minimum Fireplace Opening: 29 3/8" W x 22 3/8" H x 16 1/8" D

IDV33 INSERT	Width	Height	Depth
I33CV5 (Clean View)	37 1/8"	25 1/4"	2 5/16"
I33SR2 (Surround)	39"	27"	5/8"
I33USR4 (Surround Universal)	45"	34"	1 1/16"
I33CVPF5 (Clean View Picture Frame)	37 1/8"	25 1/4"	2 1/4"
I33SRP3 (Surround Picture Frame)	41"	31"	5/8"

Note: When Using I33CV5/I33CVPF5 Clean View a Door Frame is Required.

#### Minimum Fireplace Opening: 30 3/4" W x 25 5/8" H x 14 3/4" D

IDV43 INSERT	Width	Height	Depth
I43CV1 (Clean View)**	37 1/2"	27 1/4" / 28 3/4"	2 1/2"
I43CV3 (Clean View)**	37 3/4"	27 3/8" / 28 3/4"	4 1/8"
I43S4432 (Surround)	44"	32"	5/8"
I43US4736 (Surround Universal)	47"	36"	1 1/16"
I43SPF1 (Surround Picture Frame)	43 1/2"	33 3/8"	1 1/2"

I43CV5 (Clean View)	41 3/16"	29 1/16"	2 5/16"
I43BT4230 (Back Trim Surround)*	42"	30"	1 1/4"
I43BT4432 (Back Trim Surround)*	44"	32"	1 1/4"
I43US4736 (Surround Universal)	47"	36"	1 1/16"

\* Back Trim Surround required if the fireplace opening is smaller than 33 1/2"W x 26 5/8"H x 16 5/8".  
Note: When Using I43CV5/I43CVPF5 Clean View a Door Frame is Required.

\*\*CV1 and CV3 have a tapered profile.

#### Minimum Fireplace Opening: 33 1/2" W x 26 5/8" H x 16 5/8" D

IDV43 INSERT	Width	Height	Depth
I43CV5 (Clean View)	41 3/16"	29 1/16"	2 1/4"
I43S4432 (Surround)	44"	32"	5/8"
I43US4736 (Surround Universal)	47"	36"	1 1/16"


Note: When Using I43CV5 Clean View a Door Frame is Required.



2340 Logan Avenue  
Winnipeg, Manitoba, Canada R2R 2V3  
Phone: (204) 632-1962 Fax: (204) 632-1960  
[www.kingsmanfireplaces.com](http://www.kingsmanfireplaces.com)

## IDV33/IDV43

DIRECT VENT GAS FIREPLACE INSERT



Model IDV43N Direct Vent Insert – Natural Gas, I43CV1BL Clean View – Black, RSP10 Glass Tray Support with Bronze Glass, IDV36PRL Porcelain Reflective Liner.



\*Components may have to be ordered separately to create a complete unit. Discuss with your local Kingsman dealer for clarification.  
Kingsman Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation. Certification: The models IDV33 and IDV43 are certified for Canada/USA as a Vented Gas Fireplace Heater ANSI Z21.88-2014, CSA 2.33-2014, CGA 2.17-M91 (R2009).



CRAFTED ENTIRELY IN CANADA, EACH KINGSMAN FIREPLACE IS BUILT TO THE HIGHEST STANDARDS AND MADE TO LAST.

Printed in Canada  
09/18 – B090



### FOR CALIFORNIA RESIDENTS ONLY:

**WARNING!** This product can expose you to chemicals including Carbon Monoxide, that is an externally vented by-product of fuel consumption, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information, visit [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).