

FVF350 VENT FREE FREE STANDING GAS STOVE





THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY



2340 Logan Avenue Winnipeg, Manitoba, Canada R2R 2V3 Phone: (204) 632-1962 Fax: (204) 632-1960 www.kingsmanfireplaces.com

Model	FVFB350MVN	FVFB350/
Input Low	25,000 BTU	27,000 BT
Input High	40,000 BTU	37,000 BT
Valve Type	Millivolt	Millivolt
Efficiency	99.9%	99.9%

MVP

The ultimate in Vent-Free Free Standing Gas Stoves for new home construction or renovation, and your best choice for installation anywhere throughout your home.

STANDARD FEATURES

- Millivolt Valve with Hi-Low heat and flame adjustment and allows operation during a power failure
- Dual burner system, with realistic flame pattern
- Black Arch Door with Fixed Mesh Screen
- Equipped with 100% safety shut-off feature (ODS) Oxygen Depletion Sensor
- Black Louver
- Fibre Oak Log Set with glowing embers*
- No chimney or vent required, maximizes location flexibility
- Safety Screen Barrier

OPTIONAL FEATURES

Fan Kit

Heat activated blower with variable speed control

Thermostat

Wall Mount Millivolt Thermostat or Programmable Thermostat

Remote Control

On/Off, Thermostat On/Off, Thermostat On/Off modulating

Brick Refractory Liner

3 pieces







Fibre Oak Log Set



nement and improvements of all its products. Some aspect of units s fication: The models FVFB350MVN, FVFB350MVP Burner Systems are

MINIMUM CLEARANCES TO COMBUSTIBLES

- 12" from side of unit
- 3" from back of unit
- 3" from side of unit in corner
- 41" from top of unit



(1)

CRAFTED ENTIRELY IN CANADA, EACH KINGSMAN FIREPLACE IS BUILT TO THE HIGHEST STANDARDS AND MADE TO LAST.



FOR CALIFORNIA RESIDENTS ONLY:

WARNING! This product can expose you to chemicals including Carbon Monoxide, that is an externally vented by-product of fuel consumption, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov.



DIMENSIONS & SIZING



30 ³/8" 27 ⁵/16"

19 ¹/₁₆"

19 ¹/₁₆"