

MCVP42

ZERO CLEARANCE **DIRECT VENT** PENINSULA GAS FIREPLACE



THE DETIMATE IN DESIGN, ENGINEERING & GOALIT



MCVP42

ZERO CLEARANCE **DIRECT VENT** PENINSULA GAS FIREPLACE

Make the most of the best view in the house with our line of Zero Clearance Direct Vent Peninsula Gas Fireplaces. Ideally suited for new construction or renovations anywhere in your home.



STANDARD FEATURES

- Dedicated Clean View appliance
- Millivolt or IPI valve system allows operation during a power failure with Hi/Low heat and flame adjustment
- Safety Screen Barrier



OPTIONAL FEATURES

Porcelain Reflective Liner

Brick Refractory Liner

Traditional

Glass Tray

For use with Bronze Glass Media, Cannonballs, and Driftwood Log Set

Accent Lighting

For use with the Glass Tray

Log Set

Oak (8 piece) Set, and Driftwood (6 Piece) Set

Wall Mount Battery Holder (WMBH)

The battery holder provides power to the IPI system in case of power failures. Locating the battery holder outside of the fireplace (wall mount), provides a convenient and accessible location for battery installation and removal.

Thermostat

Wall Mount Millivolt Thermostat or Programmable Thermostat

Remote Control

Thermostat on/off, Thermostat on/off modulating, Thermostat on/off modulating and light control.





THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY

DESIGNER CLEAN VIEW™ FIREPLACES

MODEL MCVP42N/NE
Fuel Natural
Gas Control Millivolt / IPI
Input Max. 30,250 BTU
Input Min. 21,000 BTU
FE (P.4.1-15) 53% / 54.63%

Glass Type

MCVP42LP/LPE Propane Millivolt / IPI 28,500 BTU 23,000 BTU 53.82% / 55.32% Tempered

MCVP42NH/NHE Natural Millivolt / IPI 31,250 BTU 21,250 BTU 64.55% / 66.49%

MCVP42LPH/LPHE Propane Millivolt / IPI 29,000 BTU 23,000 BTU 65.66% / 67.42% Ceramic



STYLING OPTIONS



M42LOG4 Oak Log Set



M42LOG3 Driftwood Log Set



Z5GC Ember Glass (Bronze)



RBCB1 Multi-colored Cannonballs




MP42RLT Traditional Brick Liner



PL Porcelain Reflective Liner

SIZING AND DIMENSIONS





431/16" 3311/16" В С 205/8" D 2315/16" Ε F G 73/8" н 421/4" J 205/8" М 16" N 19" O

UNIT AND FRAMING DIMENSIONS

TOP FLUE MODELS MCVP42

Actual Height: 42 ½"
Framing Height: 42 ¾"
Actual Width: 43 ½"
Framing Width: 42 ½"
Actual Depth: 24 ½"
Framing Depth: 23 5½"





2340 Logan Avenue Winnipeg, Manitoba, Canada R2R 2V3 Phone: (204) 632-1962 Fax: (204) 632-1960 www.kingsmanfireplaces.com

MCVP42

ZERO CLEARANCE **DIRECT VENT** PENINSULA GAS FIREPLACE



"Components may have to be ordered separately to create a complete unit. Discuss with your local Kingsman dealer for clarification Kingsman Fireplaces maintains a program of continuous testing, refinement and improvements of all its products.

Some aspect of units shown here may be changed at any time without notice or obligation.

Certification: ANSI 221.88-2017 • CSA 2.33-2017, CSA 2.17-2017 Vented Gas Fireplace Heater.

Gas Fireplace Energy
Efficiency Rating in this brochure

Based on CSA P.4.1-15